

FENDER FLARE INSTALLATION INSTRUCTION


FORD F-150 04-08 (ALSO STYLE SIDE/FLARE SIDE)

Item No. 1ABFK00032 (Pocket Style)

Parts


Qty (1) Fender Flare Left Front (LF)
Qty (1) Fender Flare Left Rear (LR)
Qty (1) Fender Flare Right Front (RF)
Qty (1) Fender Flare Right Rear (RR)
Qty (1) Rubber Seal(enough for four flares's outer edge)

Pre-Installation




Pre-fit and ensure both left(driver side) and right(passenger side) hand fender flare to the vehicle before painting or installation. You may remove any moldings, strips or existing flares from the vehicle for fitting and installation.

Cleaning



Wash and wipe dry the areas of contact on the vehicle body. Clean the surface and inside edge of the fender flare where the rubber seal is to be attached.


Installation (Left Front Flare Shown)



Use Torx Bit to tight allen bolt & nut firmly on every pocket of the fender flare, then place the flare on the vehicle with best position. Apply 3 Lever Clips secure it to the hole with 2 existing screws and 1 expanding fastener. Apply 2 Push-In Clip into the mounting slot in flare and secure it to the vehicle. Fasten the existing factory screw into the original location that were previously removed.


Qty (2) Plastic Expanding Fastener
Qty (16) Push-In Clip
Qty (6) Lever Clip
Qty (38) Allen Bolt, Nut & Washer (Torx Bit required)
Qty (8) Self Tapping Screw (see optional B)

Painting(optional A)




Hire a professional painter or body shop and follow the paint manufacturer specifications to paint the flares. Clean all fender flares surfaces with clean water and a mild detergent before paint, do not use lacquer thinner or any solvent based products.

Apply Rubber Seal



Remove 1 inch tape liner from rubber seal, apply it on the flare, start one end & along the edge that comes in contact with body panel. **Caution: 3M tape will stick on the inside of the flare.** Make sure the rubber seal along the edge well, and rip the tape liner off gradually, apply pressure on the tape in the same time to ensure that it adheres well. Trim excess rubber seal and so on.

Installation (Left Rear Flare Shown)



Use Torx Bit to tight allen bolt & nut firmly on every pocket of the fender flare, then place the flare on the vehicle with best position. Apply 6 Push-In Clip into the mounting slot in flare and secure it to the vehicle, as shown.

Optional B: The included self tapping screw may be used for extra secure if needed.

All rights reserved by original. No part of this publication may be reproduced.