

F150 04-08 & 09-On Turn Signal Installation Manual

Items included:

1. Turn signal (LH = RH) - 1 or 2 pcs
2. LH & RH drill guide sticker - 1pcs
3. 3.6mm drill bit – 1pcs
4. Black rubber plug – 2pcs
5. This installation manual – 1pcs

Tools Needed:

1. Power drill
2. A small jewelers screwdriver
3. A flat screwdriver
4. A pair of needle pliers



1. Cut the drill guide sticker along the dotted line. Attach the correct drill guide sticker over the turn signal making sure the pre-drawn line on the sticker matches the edge of the turn signal and housing. Fold the sticker 90 degrees onto the bottom of the housing.



included black rubber plugs to block the hole or leave the hole as a rain outlet. We prefer to leave it as a rain outlet, but we provide the spare plugs if you feel otherwise.



2. Drill a small hole at the black dot position with the included 3.6mm drill bit. We prefer a cordless battery powered drill as it takes very little effort to drill thru the 3.5mm thick plastic, but any drill will do the job. (If you are not familiar with how to operate a power drill, try it on some spare plastic pieces to get the feel for it first.)

3. Remove the sticker. Insert a jewelers screwdriver and pry/push in the upward direction until you release the clip on the turn signal module. The module will gradually pop up, then you can just pull the module out from the slot as seen in the next photo (4).

4. Disconnect the plug with the help of a flat screwdriver. The plug can be quite tight when you install the new module. Put your finger on the back of the plug for support or use a pair of needle pliers to catch the plug from sliding in. After the module is inserted into the plug properly, turn on hazard light to check connection before snapping the module back into the housing.

5. After the new turn signal module is installed and working correctly, you can either utilize the



To Happy and Safe Driving!