

## Axle / Spindle Nut Torque Specification

### BHA53894

| Make  | Model       | Year    | Vehicle Notes        |       | Lb. ft | NM  |
|-------|-------------|---------|----------------------|-------|--------|-----|
| Chevy | Blazer S10  | 1991    | 4 Wheel Drive 4 Door | Front | Note A |     |
| Chevy | Blazer S10  | 1997    | 4 Wheel Drive        | Front | 103    | 140 |
| Chevy | Blazer S10  | 1992-96 | 4 Wheel Drive        | Front | 180    | 244 |
| Chevy | S10 Pickup  | 1994-96 | 4 Wheel Drive        | Front | 180    | 244 |
| Chevy | S10 Pickup  | 1997    | 4 Wheel Drive        | Front | 103    | 140 |
| GMC   | Jimmy S-15  | 1991    | 4 Wheel Drive 4 Door | Front | Note A |     |
| GMC   | Jimmy S-15  | 1992-96 | 4 Wheel Drive        | Front | 180    | 244 |
| GMC   | Jimmy S-15  | 1997    | 4 Wheel Drive        | Front | 103    | 140 |
| GMC   | S-15 Sonoma | 1994-96 | 4 Wheel Drive        | Front | 180    | 244 |
| GMC   | S-15 Sonoma | 1997    | 4 Wheel Drive        | Front | 103    | 140 |
| GMC   | Syclone     | 1991    |                      | Front | 181    | 245 |
| GMC   | Typhoon     | 1992-93 |                      | Front | 181    | 245 |
| Olds  | Bravada     | 1996    | 4 Wheel Drive        | Front | 181    | 245 |
| Olds  | Bravada     | 1991-94 | 4 Wheel Drive        | Front | 181    | 245 |

Note A      Tighten nut to 50 Lb. ft / 68 NM while turning wheel. Back off and retightne to 35 Ld. ft / 47 NM. Back off 3/8 turn. Install ring and torque locknut to 160 Lb. ft / 217 NM. Tang on ring must press through slot on spindle.

**\* Please refer to service manual if your application is not listed**