

Axle / Spindle Nut Torque Specification

BHA53993

Make	Model	Year	Vehicle Notes		Lb. ft NM
Audi	A3	2006-13		Front	Note A
Audi	TT	2008-13		Front	Note A
VW	Beetle	2012-14		Front	Note A
VW	CC	2009-13		Front	Note A
VW	Eos	2007-13		Front	Note A
VW	Golf	2011	(Built After 3/14/11 Production Date)	Front	Note A
VW	Golf	2012-13		Front	Note A
VW	GTI	2006-13		Front	Note A
VW	Jetta	2005-09	(8th Vin Digit K)	Front	Note A
VW	Jetta	2010-13		Front	Note A
VW	Passat	2006-10		Front	Note A
VW	Passat	2012-14		Front	Note A
VW	R32	2008		Front	Note A
VW	Rabbit	2006-09		Front	Note A
VW	Tiguan	2009-13		Front	Note A

Note A Vehicles with Hex bolt: Tighten bolt to 148 Lb. ft / 200 Nm with the vehicle off the ground, then lower the vehicle on to its wheels and tighten the bolt an additional 180 degrees

Vehicles with 12 point bolt without ribs on under side of bolt flange: Tighten bolt to 148 Lb. ft / 200 Nm with the vehicle off the ground, then lower the vehicle on to its wheels and tighten the bolt an additional 180 degrees

Vehicles with 12 point bolt with ribs on under side of bolt flange: Tighten bolt to 52 Lb. ft / 70 Nm with the vehicle off the ground, then lower the vehicle on to its wheels and tighten the bolt an additional 180 degrees

*** Please refer to service manual if your application is not listed**