

Axle / Spindle Nut Torque Specification

BHA52907

| Make | Model | Year | Vehicle Notes | | Lb. ft NM |
|------|----------------|---------|--------------------------------------|-------|-----------|
| Audi | A4 | 2002-07 | | Front | Note A |
| Audi | A4 | 2008 | | Front | Note B |
| Audi | A6 | 2003-04 | | Front | Note A |
| Audi | A6 V6 2.7L | 2002 | 17 Inch or 18 Inch Wheels | Front | Note A |
| Audi | A6 V8 4.2L | 1999-02 | | Front | Note A |
| Audi | A8 | 2000-03 | | Front | Note A |
| Audi | Cabriolet | 2009 | | Front | Note B |
| Audi | RS4 | 2007-08 | | Front | Note A |
| Audi | RS6 | 2003-04 | | Front | Note A |
| Audi | S4 | 2000 | (Built Before 11/99 Production Date) | Front | Note A |
| Audi | S4 | 2004-07 | | Front | Note A |
| Audi | S4 | 2008 | | Front | Note B |
| Audi | S6 | 2002-03 | | Front | Note A |
| Audi | S8 | 2001-03 | | Front | Note C |
| VW | Passat W8 4.0L | 2002-05 | 4 Motion | Front | Note A |

Note A Vehicles with 14MM bolt: Tighten to 85 Lb. ft / 115 Nm, then turn an additional 180 degree; Vehicles with 16MM bolt: Tighten to 140 Lb. ft / 190 Nm, then turn an additional 180 degrees

Note B With vehicle off the ground tighten bolt to 147 Lb. ft / 200 Nm, then turn an additional 180 degrees.

Note C With vehicle off the ground tighten bolt to 140 Lb. ft / 190 Nm, then turn an additional 180 degrees.

*** Please refer to service manual if your application is not listed**