

Axle / Spindle Nut Torque Specification

BHA54220

Make	Model	Year	Vehicle Notes		Lb. ft NM	
Audi	TT	2008-10	(Excluding Quattro Models)	Rear	Note A	
VW	CC	2009-13	(Excluding All Wheel Drive Models)	Rear	Note B	
VW	Eos	2007-13		Rear	Note B	
VW	Jetta	2005	(8th Vin Digit K)	Rear	129	175
VW	Jetta	2006		Rear	129	175
VW	Jetta	2007-10	(8th Vin Digit K)	Rear	Note C	
VW	Passat	2006	(Excluding All Wheel Drive Models)	Rear	129	175
VW	Passat	2007-10	(Excluding All Wheel Drive Models)	Rear	Note C	
VW	Tiguan	2009-13	(Excluding All Wheel Drive Models)	Rear	Note D	

Note A Vehicles with Hex bolt: Tighten bolt to 148 Lb. ft / 200 Nm with the vehicle off the ground, then lower the vehicle on to its wheels and tighten the bolt an additional 180 degrees

Vehicles with 12 point bolt without ribs on under side of bolt flange: Tighten bolt to 148 Lb. ft / 200 Nm with the vehicle off the ground, then lower the vehicle on to its wheels and tighten the bolt an additional 180 degrees

Vehicles with 12 point bolt with ribs on under side of bolt flange: Tighten bolt to 52 Lb. ft / 70 Nm with the vehicle off the ground, then lower the vehicle on to its wheels and tighten the bolt an additional 180 degrees

Note B Tighten the bolt 148 Lb. ft / 200 Nm then an additional 180 degrees

Note C Tighten the bolt 133 Lb. ft / 180 Nm then an additional 180 degrees

Note D Tighten bolt to 148 Lb. ft / 200 Nm with the vehicle off the ground, then lower the vehicle on to its wheels and tighten the bolt an additional 90 degrees

*** Please refer to service manual if your application is not listed**